

**GEO** 


## **GEO KILLER BLACK**

**Geo Killer Black** is a black ink ready to use characterized by an extraordinary washing resistance. GEO Killer Black is a high mechanical resistance ink that guarantees an incredibly soft smooth printing with a clean and unvarying tract.

Recommend for fabrics prone to dye fibrillation.

It complies with the strictest RSL restrictions thanks to its ecological features.

Great screen stability, even at high mesh count, it ensures "no dry" properties and it's easy to use.



	ca	

COLOUR 1 - RECIPE	RATIO	SCREEN	COLOUR 2 - RECIPE	RATIO	SCREEN
GEO KILLER BLACK	95	77/195	GEO KILLER BLACK	95	77/195
UNIFIX LC	5	GEL 3	UNIFIX LC	5	GEL 3
		STANDARD			STANDARD
		SQUEEGEE			SQUEEGEE
		60 SHORE			60 SHORE
COLOUR 3 - RECIPE	RATIO	SCREEN	COLOUR 4 - RECIPE	RATIO	SCREEN
COLOUII 3 - IILUII L	ILATIO	CONLECT	OULUUII T - IILUII L	ILIATIO	OULLELI
OOLOON 3 - NEON E	IIAIIO	OOTILLIT	OOLOOM 4 - NEON E	10/11/0	JOHLEH
COLOUN 3 - NEON E	TIATIO	OONLLIN	COLOGN 4 - NEON E		
COLOUN 3 - NEON E	IIAIIO	OOTILLIA	OCCOON 4 " NEON E		
COLOUN 3 - NEON E	HAHO	SQUEEGEE			SQUEEGEE

PRINTER PARAMETERS		PRINTING PROCEDURE		
DRYER TEMPERATURE	160°C - 320°F	1	PRINT DOUBLE STROKE - FLASH	
CURING TIME	2,5 MIN	2	PRINT DOUBLE STROKE - CURE	
SQUEEGEE ANGLE	25°			
PRINTING SPEED	MEDIUM			
SCREEN CLEAN UP				
USE WATER				
COMMENTS				

CII	16-24	nı.	- 4	חח	IT۱\	IFc
	ПΔ	KI.	- 4			

## SPECIAL RETARDER:

Retarder designed to further improve HYDRA, GEO and PERFETTO screen ink stability.

Add 3-5% of SPECIAL RETARDER to the inks.

Formaldehyde and phthalate free.

## **HYDRA REDUCER 120:**

To reduce viscosity, just add 3% of HYDRA REDUCER 120.

Formaldehyde and phthalate free.

## UNIFIX LC:

Additive specifically designed to ensure the proper resistance to frequent washings at high temperatures. up to 3-5% to be thoroughly mixed with the ink Phthalates and formaldehyde free **Formaldehyde and phthalate free**.





